

# SANDISK OPTIMUS™ GX PRO

# 8100

M.2 2280 NVMe™ SSD  
PCIe® 5.0 x4

## THE HIGH-PERFORMANCE PCIe® 5.0 SSD FOR UNCOMPROMISING PROFESSIONALS, CREATORS AND GAMERS.

Professionals, creators, and gamers deserve optimal storage performance for demanding AI workflows and intense gaming sessions. The SANDISK Optimus™ GX PRO 8100 NVMe™ SSDs are designed to deliver exactly that. With groundbreaking PCIe® 5.0 storage performance, this SSD reaches Sequential Read/Write speeds up to 14,900/14,000 MB/s<sup>2</sup> (2TB<sup>1</sup> and 4TB<sup>1</sup> models). Seamlessly multitask with Random Read/Write speeds up to 2.3M/2.4M IOPS<sup>2</sup> (2TB<sup>1</sup> and 4TB<sup>1</sup> models), and transfer files faster thanks to integrated SANDISK® nCache™ 4.0 technology. Store expansive game libraries and large digital assets with capacities up to 8TB<sup>1</sup> on M.2 2280 built with the 8th generation of our trusted SANDISK® BiCS TLC 3D CBA NAND. Engineered to endure write intensive workflows, the SANDISK Optimus™ GX PRO 8100 SSD offers a 4,800 TBW<sup>4</sup> (8TB<sup>1</sup> model) endurance rating. Ideal for compatible workstations, AI PCs, gamer PCs, and creator PCs.



### KEY FEATURES

- **SERIOUS PCIe® 5.0 SPEEDS**  
Sequential Read/Write speeds up to 14,900/14,000 MB/s<sup>2</sup> (2TB<sup>1</sup> and 4TB<sup>1</sup> models) lets you quickly load and store massive projects.
- **SUPERCHARGE AI WORKFLOWS**  
Demanding AI workflows are supercharged with Random Read/Write speeds up to 2.3M/2.4M IOPS<sup>2</sup> (2TB<sup>1</sup> and 4TB<sup>1</sup> models) and integrated SANDISK® nCache™ 4.0 technology.
- **ROOM FOR YOUR IMMENSE LIBRARIES**  
Gamers and professionals with vast libraries can be worry-free with capacities up to 8TB<sup>1</sup> on M.2 2280 built with 8th Generation SANDISK® BiCS TLC 3D CBA NAND.
- **AN INDUSTRY LEADER IN POWER EFFICIENCY**  
Enjoy over 2x higher power efficiency than our PCIe® Gen 4 SSD<sup>12</sup> for on-the-go productivity and sustained gaming performance.
- **DURABILITY FOR CREATORS**  
With up to 4,800 TBW<sup>4</sup> (8TB<sup>1</sup> model) endurance rating, your drive is designed for write-intensive workloads such as content creation tools and AI-enabled video editors.
- **PEACE OF MIND**  
To champion professionals in their work and play, Sandisk provides a 5-year limited warranty<sup>5</sup> for ultimate peace of mind.

**PRODUCT FEATURES**

**ONE OF THE FASTEST PCIe® 5.0 DRIVES OUT THERE**

Whether you're pushing the boundaries at work or play, the SANDISK Optimus™ GX PRO 8100 SSD keeps up with you. Load and store massive assets, projects, and games thanks to blazingly fast Sequential Read/Write speeds of up to 14,900/14,000 MB/s<sup>2</sup> (2TB<sup>1</sup> and 4TB<sup>1</sup> models).

**PUSHING LIMITS DEMANDS HIGHER STORAGE CAPACITIES**

Application datasets, 8K video, full frame images, and AAA games have one thing in common: they can get massive. With capacities up to 8TB<sup>1</sup> on an M.2 2280 form factor built with the 8th generation of our trusted SANDISK® BiCS TLC 3D CBA NAND, you have room for what matters.

**ENGINEERED TO ENDURE WRITE-INTENSIVE WORKLOADS**

With up to 4,800 TBW<sup>4</sup> (8TB<sup>1</sup> model) endurance rating, your drive is designed to handle heavy, write-intensive workloads, like scientific and financial simulation, 3D modeling, and AI production workflows.

**LIGHTNING-FAST PERFORMANCE FOR SUPERCHARGED AI WORKFLOWS**

All models perform optimally with fast Random Read/Write speeds, and this SSD offers just that. With up to 2.3M/2.4M IOPS<sup>2</sup> (2TB<sup>1</sup> and 4TB<sup>1</sup> models) and our integrated SANDISK® nCache™ 4.0 technology, this SSD delivers blistering burst write performance for large file transfers.

**RUNNING FAST AND STAYING COOL**

With over 2x more power efficiency (1TB<sup>1</sup> – 4TB<sup>1</sup> models) than our PCIe® Gen 4.0<sup>12</sup> SSD at an average operating power of 7.5W<sup>3</sup> or under, your SSD stays cool and delivers high performance over a longer period.

**PEACE OF MIND COMES STANDARD**

This SSD comes with a 5-year limited warranty<sup>5</sup> and support for TCG Opal v2.02 for data-at-rest encryption,<sup>10</sup> allowing you to focus on what you do best.

**PRODUCT SPECIFICATIONS**

CAPACITIES <sup>1</sup>	1TB	2TB	4TB	8TB
<b>MODEL NUMBERS</b>	SDSP82100TAN	SDSP82200TAN	SDSP82400TAN	SDSP82800TAN
<b>FORM FACTOR</b>	M.2 2280-S3-M			M.2 2280-D5-M
<b>INTERFACE<sup>11</sup></b>	PCIe® 5.0 x4 NVMe™ 2.0			
<b>NAND</b>	SANDISK® TLC 3D CBA NAND			
<b>DRAM CACHE</b>	Yes			
<b>SLC CACHE</b>	SANDISK® nCache™ 4.0			
<b>PERFORMANCE<sup>2</sup></b>				
Sequential Read 1MB (MB/s) up to (Queue Depth=8, Threads=1)	14,900MB/s	14,900MB/s	14,900MB/s	14,900MB/s
Sequential Write 1MB (MB/s) up to (Queue Depth=8, Threads=1)	11,000MB/s	14,000MB/s	14,000MB/s	13,200MB/s
Random Read 4KB (IOPS) up to (Queue Depth=32, Threads=16)	1.6M IOPS	2.3M IOPS	2.3M IOPS	2.2M IOPS
Random Write 4KB (IOPS) up to (Queue Depth=32, Threads=16)	2.4M IOPS	2.4M IOPS	2.4M IOPS	2.4M IOPS
<b>POWER<sup>3</sup></b>				
Average Active Power Read	6.2 W	6.4 W	6.5 W	7.1 W
Average Active Power Write	6.1 W	7.0 W	7.0 W	7.3 W
Sleep (PS4)	5 mW			
<b>RELIABILITY</b>				
Endurance <sup>4</sup> (TBW)	600	1,200	2,400	4,800
MTTF <sup>4</sup> up to (hours)	1.75M Hours			
Limited Warranty <sup>5</sup>	5 years			
<b>REGULATORY</b>				
Certifications	BSMI, CAN ICES-3(B)/NMB-3(B), CB-Scheme, CE, FCC, KCC, Morocco, RCM, TÜV, UL, VCCI, UKCA			
RoHS Compliance	Yes			
<b>SECURITY</b>	TCG OPAL 2.02 <sup>10</sup>			
<b>FEATURED SOFTWARE</b>	SANDISK® Dashboard <sup>6</sup> (Windows® only), Acronis® True Image™ for SANDISK® software <sup>7</sup>			
<b>ENVIRONMENTAL</b>				
Operating Temperature <sup>8</sup>	32°F to 185°F (0°C to 85°C)			
Non-Operating Temperature <sup>8</sup>	-40°F to 185°F (-40°C to 85°C)			
Operating Vibration	5 gRMS, 10-2000 Hz, 3 axes			
Non-operating Vibration	4.9 gRMS, 7-800 Hz, 3 axes			
Shock	1,500G @ 0.5 ms half-sine			
<b>DIMENSIONS<sup>9</sup></b>				
	Length	Width	Height	Weight
1TB-4TB <sup>1</sup>	80mm	22mm	2.38mm	7.5g
8TB <sup>1</sup>	80mm	22mm	3.88mm	8.6g

<sup>1</sup> 1GB = 1 billion bytes and 1TB = 1 trillion bytes. Actual user capacity may be less depending on operating environment.  
<sup>2</sup> 1MB/s = 1 million bytes per second. IOPS = input/output operations per second. Based on internal testing; performance may vary depending upon host device, usage conditions, drive capacity, and other factors.  
<sup>3</sup> Average Power – Read and Average Power – Write are measured using IOMeter 1.1.0 during a burst sequential read and write operation (measured separately) and represent a moving average over a 10 second period. Performance may vary depending on test setup, configuration and firmware version.  
<sup>4</sup> TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity. MTTF = Mean Time To Failure based on internal testing using Telcordia™ stress part testing (Telcordia SR-332, GF, 25°C). MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty.  
<sup>5</sup> 5 years or Max Endurance (TBW) limit, whichever occurs first. See support.sandisk.com for region-specific warranty details.  
<sup>6</sup> Available for download at sandisk.com/support  
<sup>7</sup> Download, installation and administrative privileges required. Includes 5-year license for your compatible drive. Redeem within 90 days of purchase. Terms and conditions apply. User account registration may be required. May not be combined with other offers. Limited time offer; see sandisk.com/support for more details. Offer subject to change.  
<sup>8</sup> Operational temperature is defined as temperature reported by the drive. Note that drive temperature readings are expected to be higher than ambient temperature when the SSD is placed inside a system. The SSD box package is rated up to 60°C. Non-operational storage temperature does not guarantee data retention.  
<sup>9</sup> Physical product dimensions for length and width may vary by ± 0.15mm and product weight may vary by ± 1g.  
<sup>10</sup> Requires motherboard BIOS or third-party software to enable.  
<sup>11</sup> Backwards compatible with PCIe® 4.0 x4, 4.0 x2, 4.0 x1, 3.0 x4, 3.0 x2, 3.0 x1, 2.0 x4, 2.0 x2 and 2.0 x1.  
<sup>12</sup> Over 2x more power efficient than the 1TB, 2TB, and 4TB SANDISK Optimus™ GX PRO 850X NVMe™ SSDs.



SANDISK, the SANDISK logo, SANDISK Optimus, and nCache are registered trademarks or trademarks of Sandisk Corporation or its affiliates in the U.S. and/or other countries. Acronis and True Image are registered trademarks of Acronis International GmbH in the United States and other countries. Windows and Microsoft are registered trademarks of the Microsoft group of companies. The NVMe word mark is a trademark of NVM Express, Inc. PCIe® is a registered trademark of PCI-SIG. All other marks are the property of their respective owners. Product specifications subject to change without notice. Pictures shown may vary from actual products.  
 © 2025 Sandisk Corporation or its affiliates. All rights reserved.