



## Western Digital® iNAND® IX EM132 Industrial Embedded Flash Devices

### Proven Reliability and Endurance for Embedded Platforms

The Industrial iNAND IX EM132<sup>1</sup> Embedded Flash Drive (EFD) is Western Digital's most advanced e.MMC flash storage solution for industrial applications, with high reliability and endurance across a wide range of operational requirements.

Designed and tested to withstand demanding environmental conditions, these industrial grade flash devices feature advanced flash memory management firmware that provides enhanced power immunity, ECC, wear leveling, and bad block management. Data intensive applications can rely on the EM132 to capture every critical moment, log each event, and to ensure quality-of-service to end-users.

The Smart Partitioning feature of the iNAND IX EM132 EFD Industrial flash devices enables Boot partitions, RPMB, multiple General-Purpose Partitions, User Data Area and Enhanced User Data Area, providing OEMs the flexibility to choose different attributes on a single device depending on storage requirements.

With optimized 3D NAND memory, iNAND IX EM132 offers a significant capacity increase compared with the previous generation of iNAND products.

### Business Benefits

- Drives faster time to market with quick system integration
- Enables real-time analytics at the edge
- Enables cloud augmentation, reduces network traffic
- Improves connected user experience
- Provides reliable local storage, as primary or backup
- Optimizes system performance
- Improves cost per MB over 2D memory

### Serving Industrial Applications

- Industrial boards and PCs
- Factory automation
- Medical
- Smart meters and utilities
- Smart buildings and homes
- IoT gateways
- Surveillance
- Drones
- SOM
- Transportation
- Networking

### Key Features and Benefits

- Operating Temperature Range: -25°C to 85°C (16GB-256GB) on Industrial and Commercial SKUs; -40°C to 85°C (32GB-256GB) on Industrial Extended-Temperature SKUs
- Broad Portfolio: 16GB to 256GB
- Extended product life cycle for industrial grade
- Advanced controller built for endurance and reliability
- High Endurance: Up to 3K P/E cycles in TLC
- Smart Partitioning, Advanced Health Report and Manual Refresh (Industrial Grade)
- Enhanced User Data Area (EUDA)
- Operating voltage: 2.7V to 3.6V

# Western Digital® iNAND® IX EM132<sup>1</sup> Industrial Embedded Flash Devices

## PRODUCT BRIEF

### Specifications

	16GB	32GB	64GB	128GB	256GB
Interface	eMMC 5.1 HS400	eMMC 5.1 HS400	eMMC 5.1 HS400	eMMC 5.1 HS400	eMMC 5.1 HS400
Form Factor (mm)	11.5mm x 13mm x 1.0mm	11.5mm x 13mm x 1.0mm	11.5mm x 13mm x 1.0mm	11.5mm x 13mm x 1.0mm	11.5mm x 13mm x 1.2mm
NAND Flash Technology	3D NAND BiCS3 64L	3D NAND BiCS3 64L	3D NAND BiCS3 64L	3D NAND BiCS3 64L	3D NAND BiCS3 64L
Formatted Capacity <sup>2</sup>	16GB	32GB	64GB	128GB	256GB
<b>Operating Voltage</b>					
Core Voltage (VCC):	2.7-3.6V	2.7-3.6V	2.7-3.6V	2.7-3.6V	2.7-3.6V
I/O (VCCQ) Voltage	1.7-1.95V or 2.7-3.6V	1.7-1.95V or 2.7-3.6V	1.7-1.95V or 2.7-3.6V	1.7-1.95V or 2.7-3.6V	1.7-1.95V or 2.7-3.6V
<b>Operating Temperature</b>					
Industrial Wide Temperature	-25°C to 85°C	-25°C to 85°C	-25°C to 85°C	-25°C to 85°C	-25°C to 85°C
Industrial Extended Temperature		-40°C to 85°C	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
<b>Performance<sup>3</sup></b>					
Sequential Read/Write (MB/s)	Up to 310/150	Up to 310/150	Up to 310/150	Up to 310/150	Up to 310/150
Random Read/Write (IOPS)	Up to 20K/12.5K	Up to 20K/12.5K	Up to 20K/12.5K	Up to 20K/12.5K	Up to 20K/12.5K
<b>Write Endurance</b>					
Total Terabytes Written (TBW)	Up to 693TBW				
<b>Ordering Information</b>					
Commercial Grade	SDINBDA6-16G	SDINBDA6-32G	SDINBDA6-64G	SDINBDA6-128G	SDINBDA6-256G
Industrial Wide Temperature	SDINBDA6-16G-I1	SDINBDA6-32G-I1	SDINBDA6-64G-I1	SDINBDA6-128G-I1	SDINBDA6-256G-I1
Industrial Extended Temperature		SDINBDA6-32G-XI1	SDINBDA6-64G-XI1	SDINBDA6-128G-XI1	SDINBDA6-256G-XI1

#### Footnotes:

<sup>1</sup> Formerly known as iNAND 7550I.

<sup>2</sup> 1 GB = 1,000,000,000 bytes, 1TB = 1 trillion bytes. Actual user capacity may be less due to operating environment.

<sup>3</sup> Performance will vary by capacity point or with the changes in useable capacity. Consult product manual for further details.

## Western Digital.

5601 Great Oaks Parkway  
San Jose, CA 95119, USA  
US (Toll-Free): 877.816.5740  
International: 408.717.6000  
www.westerndigital.com

© 2021 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, and iNAND are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. Pictures shown may vary from actual products. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit our website, <http://www.westerndigital.com> for additional information on product specifications.